



PRODUCT DETAILS




Easy Clean technology: Rotary dial on »Filter«

The UVC clarifier eliminates algae and reduces pathogens. Then the "treated" water flows through the fine mechanical and large-pored biological filter elements of the filter unit that decompose the pollutants and clarify the water.



Easy Clean technology: Rotary dial on »Clean«

Turning the rotary dial activates the cleaning function. Then move the cleaning lever up and down to »squeeze out« the filter elements. Simultaneously clean water flows into the filter and forces the polluted water out of the unit, that decomposes pollutants and clarifies the water.



Accessories

Replacement bulbs

UVC 9 W	Item no.	54984	Page 148
UVC 11 W	Item no.	56112	Page 148
UVC 18 W	Item no.	56236	Page 148
UVC 24 W	Item no.	56237	Page 148
UVC 36 W	Item no.	55432	Page 148
UVC 55 W	Item no.	56636	Page 148

Replacement foam sets

FiltoClear 3000	Item no.	56109	Page 136
FiltoClear 6000	Item no.	56110	Page 136
FiltoClear 12000	Item no.	51255	Page 136
FiltoClear 16000	Item no.	51258	Page 136
FiltoClear 20000 / 30000	Item no.	51290	Page 136

FiltoCap sand

Decorative rock cover suitable for all BioPress and FiltoClear filters.

Item no. 50420 Page 294



AquaActiv BioKick 200 ml

To achieve the optimal filter effect »treatment« with OASE BioKick filter starter is recommended. This should be added each time the filter is placed in service (e.g. spring).

Item no. 50295 Page 192



TECHNICAL DATA

Matching filters and filter systems starting on page 64

		FiltoClear 3000	FiltoClear 6000	FiltoClear 12000	FiltoClear 16000	FiltoClear 20000	FiltoClear 30000
Dimensions (Ø x H)	mm	380 x 310	380 x 430	380 x 510	380 x 630	380 x 750	
Rated voltage		230 V / 50 Hz		220 - 240 V / 50/60 Hz			
Power consumption	W	14	15	18	24	36	55
Power cable length	m				5.00		
Net weight	kg	5.58	6.18	7.10	7.90	8.60	9.00
Guarantee (+ request guarantee)	Years				2 + 1		
UVC power	W	9	11	18	24	36	55
Number of blue filter foams	Unit	2	3			4	5
Number of red filter foams	Unit	1	3	2	3	4	
Pollutant level indicator					Yes		
Temperature display					No		
Connection inlet	mm	19 / 25 / 32 / 38			38 / 50		
Connection inlet		¼", 1", 1 ¼", 1 ½"			1 ½", 2"		
Connections, outlet	mm	19 / 25 / 32 / 38			38 / 50		
Connections, outlet		¼", 1", 1 ¼", 1 ½"			1 ½", 2"		
Connections, sludge discharge	mm	19 / 25 / 32 / 38			38 / 50		
Connections, sludge discharge		¼", 1", 1 ¼", 1 ½"			1 ½", 2"		
Max. flow rate	l/h	4000	6000	8000	10000	12000	
Max. operating pressure	bar				0.2		
Suitable for ponds up to max.	m³	3.0	6.0	12.0	16.0	20.0	30.0
Suitable for ponds with fish stock	m³	1.5	3.0	6.0	8.0	10.0	15.0
Suitable for ponds with koi ¹⁾	m³	-	1.5	3.0	4.0	5.0	7.5
Item no. (GB-Version)		56052		51245	51248	50580	50581
Item no.		55997	55998	51244	51247	50576	50577